



A7000 – Interior Alkyd Satin/Semi

Technical Specifications

PRODUCT DESCRIPTION			
The A7000 Line - Interior Alkyd Satin/Semi is a pure Soya Alkyd finish exhibiting excellent hiding, flow and leveling and gloss retention. A7300's sheen is on the high end of a satin finish and the low end of a semi-gloss finish.			
SPECIFICATIONS			
Type:	Soya Alkyd	Dry Time - Touch:	4-6 Hours
Sizes:	1's, 5's and Quarts	Dry Time - Recoat:	12-16 Hours
Bases:	White, Pastel, Midtone, Accent	Full Service:	14 Days
Gloss:	25%-35% @ 60°	Flash Point:	41° C (TCC)
		VOC:	362 gm/L
		% Solids Volume:	53 +/- .5
		Weight Per Gallon:	12.01 +/- .2
PRODUCT USE			
<p style="text-align: center;">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Wood: Sand entire surface and apply one coat of either C₂ Sandable Acrylic Primer or C₂ Alkyd Enamel Undercoater. Allow primer to dry. If necessary sand smooth entire surface. Apply one or two coats of C₂ Interior Alkyd Satin/Semi.</p> <p>Previously Painted Surfaces: Remove loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C₂ Drywall Primer or C₂ Alkyd Enamel Undercoater. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C² Interior Alkyd Satin/Semi.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints and repaired areas with C₂ Drywall Primer, after dry apply one coat of C₂ Drywall primer to the entire surface. Finish with one or two coats of C₂ Interior Alkyd Satin/Semi.</p>		<p style="text-align: center;">Application</p> <p>A7300 Interior Alkyd Satin/Semi may be applied by roller (no more than 3/8 inch nap), brush (pure china bristle) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using mineral spirits.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			

