



A9100- Exterior Alkyd Primer

Technical Specifications

PRODUCT DESCRIPTION

A9100 Exterior Alkyd Primer is a pure Soya Alkyd Primer exhibiting excellent sealing, stain blocking and mildew resistance characteristics for application in most residential or commercial environments. **A9100 Exterior Alkyd Primer** is specifically formulated to seal most common exterior stains and will adhere tenaciously to a variety of surfaces.

SPECIFICATIONS

Type:	Pure Soya Alkyd	Dry Time – Touch:	2 to 4 hours
Sizes:	1's and 5's	Dry Time – Recoat:	8 to 12 hours
Bases:	None available	Full Service:	14 days
Gloss:	0 to 5% at 60⁰	Flash Point:	41⁰ C (TCC)
	0 to 5% at 85⁰	VOC:	347 grams/liter
		% Solids Vol:	54 – 55
		Weight Per Gallon:	11.66 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Free surface of all contaminants such as dirt, dust, oil, grease, wax, and rust. Remove mildew using a chlorine bleach solution of 1 to 4 ratio of bleach to water. Patch holes and cracks, sand smooth and remove sanding dust.

New Wood: **Sand smooth and remove dust. Spot Prime all knots with C₂ Exterior Alkyd Primer. Apply one coat of C₂ Exterior Alkyd Primer to entire surface.**

Painted Surfaces: **Remove loose and peeling paint. Dull glossy areas. Apply one coat of C₂ Exterior Alkyd Primer.**

Application

A9100 Exterior Alkyd Primer may be applied by roller (no more than 3/8-inch nap), brush (pure china bristle) or spray.

Spreading Rate: **Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).**

Thinning: **Do not thin.**

Airless Spray: **Use a 12 to 15 mil size tip.**

Cleanup: **Clean painting equipment and spills immediately using mineral spirits.**

Limitations: Do not apply if product, air, or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. **Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.**

Disposal: **Do not dispose of any paint product or solvent in drains, sewers, or municipal garbage. See your C₂ dealer for disposal recommendations in your area.**

C² Paint is formulated without lead or mercury