



## C4000 – Interior Latex Non-Reflective Flat Technical Specifications

<b>PRODUCT DESCRIPTION</b>			
<p>The C4000 line –Interior Latex Non-Reflective Flat is a 100% Co-Polymer resin formulation designed to produce an exceptionally non-reflective (flat) surface on interior walls and ceilings no matter the color selected. The C4000 series is an exceptionally scrubable flat finish with good washability and excellent application properties resulting in a smooth, beautiful finish that is unsurpassed.</p>			
<b>SPECIFICATIONS</b>			
<b>Type:</b>	Co-polymer acrylic	<b>Dry Time - Touch:</b>	30 Minutes
<b>Sizes:</b>	1's, 5's and Quarts	<b>Dry Time - Recoat:</b>	2-4 Hours
<b>Bases:</b>	White, Pastel, Midtone, Accent	<b>Full Service:</b>	7 Days
<b>Gloss:</b>	2.2 max @ 60°	<b>Flash Point:</b>	None
	2.0 max @ 85°	<b>VOC:</b>	106 gm/L
		<b>% Solids Volume:</b>	42.5 +/- .5
		<b>Weight Per Gallon:</b>	12.67 +/- .2
<b>PRODUCT USE</b>			
<p style="text-align: center; color: red; font-weight: bold;">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p><b>New Plaster &amp; Drywall:</b> Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints and repaired areas with C<sub>2</sub> Drywall Primer, after dry apply one coat of C<sub>2</sub> Drywall primer to the entire surface. Finish with one or two coats of C<sub>2</sub> Interior Latex Non-Reflective Flat.</p> <p><b>Previously Painted Surfaces:</b> Remove loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C<sub>2</sub> Drywall Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C<sub>2</sub> Interior Latex Non-Reflective Flat.</p> <p><b>New Wood:</b> Sand entire surface and apply one coat of either C<sub>2</sub> Sandable Acrylic Primer or C<sub>2</sub> Alkyd Enamel Undercoater. Allow primer to dry. If necessary sand smooth entire surface. Apply one or two coats of C<sub>2</sub> Interior Latex Non-Reflective Flat.</p>		<p style="text-align: center; color: red; font-weight: bold;">Application</p> <p>C4000 Interior Latex Non-Reflective Flat may be applied by roller (no more than 3/8 inch nap), brush (synthetic) or spray.</p> <p><b>Spreading Rate:</b> Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p><b>Thinning:</b> Do not thin.</p> <p><b>Airless Spray:</b> Use a 12 to 15 mil size tip.</p> <p><b>Cleanup:</b> Clean painting equipment and spills immediately using warm soapy water.</p> <p><b>Limitations:</b> Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Deep colors in a flat finish will burnish. For a non-burnishing finish, choose C<sub>2</sub> Premium Eggshell. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p><b>Disposal:</b> Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C<sub>2</sub> dealer for disposal recommendations in your area.</p>	

<b>C2 Paint is formulated without lead or mercury</b>	