



C4100 - Interior Latex Flat

Technical Specifications

PRODUCT DESCRIPTION			
C4100 Interior Latex Eggshell is a 100% acrylic formulation designed for application in most residential or commercial applications. C4100 is specifically formulated to provide outstanding covering power, stain resistance and washability.			
SPECIFICATIONS			
Type:	Acrylic Resin	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's and Quarts	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Midtone	Full Service:	7 Days
Gloss:	2%-6% @ 85°	Flash Point:	None
		VOC:	100
		% Solids Volume:	43.3
		Weight Per Gallon:	12.04
PRODUCT USE			
<p style="text-align: center; color: red; margin: 0;">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat C2000 Interior Latex Primer to entire surface. Finish with one or two coats of C² Interior Latex Flat.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2000 Interior Latex Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C² Interior Latex Flat.</p> <p>New Wood: Sand entire surface and apply one coat of either C2000 Interior Latex or A6000 Interior Alkyd Primer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C² Interior Latex Flat.</p>		<p style="text-align: center; color: red; margin: 0;">Application</p> <p>C4100 Interior Latex Flat may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead, mercury or formaldehyde			